

SAFETY DATA SHEET

1. Identification

Product identifier	R4 PROTECTIVE COATING REMOVER
Other means of identification	
Product code	R4
Recommended use	Protective coating remover.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer/Supplier	Granitize Products, Inc. 11022 Vulcan Street South Gate, CA 90280-0893 US (562) 923-5438
Telephone:	CHEMTREC: (800) 424-9300
Emergency	CHEMTREC International: 00 1-703-527-3887

2. Hazard(s) identification

Physical hazards	Flammable Liquids	Category 3
Health Hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Specific Target Organ Toxicity, Single Exposure	Category 3 respiratory tract irritation
	Specific Target Organ Toxicity, Single Exposure	Category 3 narcotic effects
	Specific Target Organ Toxicity, Repeated Exposure	Category 1 (Central nervous system)
Environmental hazards	Aspiration hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Causes damage to organs (Central nervous system) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing.
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Stoddard solvent	8052-41-3	20-40
2-Propanol	67-63-0	20-30
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-30
Polyalkyl siloxane	63148-62-9	10-20
1,2,4-Trimethylbenzene	95-63-6	1-10
1,3,5-Trimethylbenzene	108-67-8	1-5
Diethylbenzene	25340-17-4	0.1-5.0
Cumene	98-82-8	0.1-1.0
Xylene	1330-20-7	0.1-1.0

Composition comments Components not listed are either non-hazardous or are below reportable limits. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
Skin contact	Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
Ingestion	If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention.
Most important symptoms/effects, acute and delayed	Irritating to eyes, respiratory system and skin. May be fatal if swallowed and enters airways. Causes damage to organs (Central nervous system) through prolonged or repeated exposure. Suspected of causing cancer. May cause drowsiness or dizziness.
Indication of immediate medical attention and special treatment needed	In case of shortness of breath, give oxygen. Keep victim warm. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
General information	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Swallowing or vomiting of the liquid may result in aspiration into the lungs. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical	The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.
General fire hazards	The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material. Small Spills: Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling	The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care.
Conditions for safe storage, including any incompatibilities	Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Propanol (CAS 67-63-0)	PEL	980 mg/m3 400 ppm
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3 500 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm
1,3,5-Trimethylbenzene (CAS 108-67-8)	TWA	25 ppm
2-Propanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Cumene (CAS 98-82-8)	TWA	50 ppm
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
		25 ppm
1,3,5-Trimethylbenzene (CAS 108-67-8)	TWA	125 mg/m3
		25 ppm
2-Propanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm
Cumene (CAS 98-82-8)	TWA	245 mg/m3
		50 ppm
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3
	TWA	350 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Diethylbenzene (CAS 25340-17-4)	TWA	5 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Propanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines Follow standard monitoring procedures.

US - California OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear goggles/face shield.

Skin protection	
Hand protection	Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that is specifically recommended by the Personal Protective Equipment manufacturer.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Appearance	Light blue liquid.
Physical state	Liquid.
Form	Not available.
Color	Light blue.
Odor	Alcohol odor.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	231 - 233 °F (110.56 - 111.67 °C)
Flash point	104.0 °F (40.0 °C)
Evaporation rate	2.4 (N-butyl acetate = 1)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Completely soluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Percent volatile	90 - 95 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Electrostatic discharge.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon monoxide. Carbon dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause respiratory irritation. May cause drowsiness or dizziness.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Irritating to eyes, respiratory system and skin. May be fatal if swallowed and enters airways. Suspected of causing cancer. Causes damage to organs (Central nervous system) through prolonged or repeated exposure. May cause drowsiness or dizziness.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	10200 mg/m3, 4 Hours
<i>Oral</i>		
LD50	Rat	6000 mg/kg
1,3,5-Trimethylbenzene (CAS 108-67-8)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	10200 mg/m3, 4 Hours
<i>Oral</i>		
LD50	Rat	6000 mg/kg
2-Propanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	16000 ppm, 8 hours > 10000 ppm, 6 Hours
<i>Oral</i>		
LD50	Rat	5045 mg/kg 5.84 g/kg
Cumene (CAS 98-82-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg, 24 Hours

Components	Species	Test Results
<i>Inhalation</i>		
LC50	Rat	8000 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	2260 mg/kg
Diethylbenzene (CAS 25340-17-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	2520 - 5000 mg/kg 2050 ml/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg 17.8 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	> 8000 ppm, 20 Minutes
	Rat	4000 ppm
<i>Oral</i>		
LD50	Rat	5.46 g/kg
<i>Other</i>		
LD50	Mouse	17.81 mm/kg
Polyalkyl siloxane (CAS 63148-62-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	>= 5000 mg/kg
<i>Oral</i>		
LD50	Rat	>= 17000 mg/kg
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 4.96 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 4800 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not classified.	
Skin sensitization	Not a skin sensitizer.	
Germ cell mutagenicity	Not classified.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.	

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to the following organs through prolonged or repeated exposure: Central nervous system.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	May cause central nervous system effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)			
Aquatic			
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	7.19 - 8.28 mg/l, 96 hours
1,3,5-Trimethylbenzene (CAS 108-67-8)			
Aquatic			
Fish	LC50	Goldfish (<i>Carassius auratus</i>)	9.89 - 15.05 mg/l, 96 hours
2-Propanol (CAS 67-63-0)			
Aquatic			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/l, 96 hours
Cumene (CAS 98-82-8)			
Aquatic			
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.)	3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	2.7 mg/l, 96 hours
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)			
Aquatic			
<i>Acute</i>			
Crustacea	EL50	Daphnia	4.5 mg/l, 48 hours
Fish	LL50	Oncorhynchus mykiss	10 mg/l, 96 hours

Persistence and degradability Not available.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Propanol (CAS 67-63-0)	0.05
Stoddard solvent (CAS 8052-41-3)	3.16 - 7.15

Mobility in soil The product is water soluble and may spread in water systems.

Other adverse effects The product is a volatile organic compound which has a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 °F
Waste codes should be assigned by the user based on the application for which the product was used.

US RCRA Hazardous Waste U List: Reference

Cumene (CAS 98-82-8) U055

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (Stoddard solvent, 2-Propanol RQ = 648 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, B1, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (2-Propanol, Stoddard solvent)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	Yes
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1268
UN proper shipping name	Petroleum products, n.o.s. (2-Propanol, Stoddard solvent)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
--------------------------	---

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
2-Propanol	67-63-0	20-30
1,2,4-Trimethylbenzene	95-63-6	1-10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance**Safe Drinking Water Act (SDWA)** Not regulated.**US state regulations**

WARNING: This product contains chemicals known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,3,5-Trimethylbenzene (CAS 108-67-8)
 2-Propanol (CAS 67-63-0)
 Cumene (CAS 98-82-8)
 Stoddard solvent (CAS 8052-41-3)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,3,5-Trimethylbenzene (CAS 108-67-8)
 2-Propanol (CAS 67-63-0)
 Cumene (CAS 98-82-8)
 Diethylbenzene (CAS 25340-17-4)
 Stoddard solvent (CAS 8052-41-3)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
 1,3,5-Trimethylbenzene (CAS 108-67-8)
 2-Propanol (CAS 67-63-0)
 Cumene (CAS 98-82-8)
 Stoddard solvent (CAS 8052-41-3)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
 2-Propanol (CAS 67-63-0)
 Cumene (CAS 98-82-8)

US. California Proposition 65**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Cumene (CAS 98-82-8)
 Ethylbenzene (CAS 100-41-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	21-August-2014
Revision date	-
Version #	01
Further information	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
NFPA ratings	
References	ACGIH EPA: Acquire database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents
Disclaimer	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.